

In The Specification:

Please replace the paragraph at page 1, lines 7-8 with the following replacement paragraph:

This application is a ~~division~~ divisional patent application of U.S. Patent Application Serial No. 09/496,831, filed on February 2, 2000, now U.S. Patent No. 6,630,531.

Please replace the paragraph at page 14, lines 3-18 with the following replacement paragraph:

The adhesive can also be provided in the form of a pressure-sensitive adhesive transfer tape in which at least one layer of the adhesive is disposed on a release liner for application to a permanent substrate at a later time. The adhesive can also be provided as a single coated or double coated tape in which the adhesive is disposed on a permanent backing. Backings can be made from plastics (e.g., polypropylene, including biaxially oriented polypropylene, vinyl, polyethylene, polyester such as polyethylene terephthalate), nonwovens (e.g., papers, cloths, nonwoven scrims), metal foils, foams (e.g., polyacrylic, polyethylene, polyurethane, neoprene), and the like. Foams are commercially available from various suppliers such as 3M Co., Voltek, Sekisui, and others. The foam may be formed as a coextruded sheet with the adhesive on one or both sides of the foam, or the adhesive may be laminated to it. When the adhesive is laminated to a foam, it may be ~~desireable~~ desirable to treat the surface to improve the adhesion of the adhesive to the foam or to any of the other types of backings. Such treatments are typically selected based on the nature of the materials of the adhesive and of the foam or backing and include primers and surface modifications (e.g., corona treatment, surface abrasion).